

GE Healthcare

LOGIQ P9

Make it easy. Make it your own.

Product description

The LOGIQ™ P9 is a highly capable ultrasound system that provides excellent image quality and productivity through easy to use tools across a wide range of applications in a portable, ergonomic, budget-friendly system design.¹



General Specification

System Overview

Dimensions and Weight:	
Height	Articulating monitor arm (option) 1320 mm ~ 1570 mm (52.0 in ~ 61.8 in)
Width	Keyboard: 430 mm (16.9 in) Foot cover: 495 mm (19.5 in) Monitor: 525 mm (20.7 in)
Depth	Foot cover: 685 mm (27.0 in) Rear handle: 740 mm (29.1 in)
Weight (No Peripherals)	60 kg/132 lbs

Electrical Power	
Voltage	100 – 240 Vac
Frequency	50/60 Hz
Power consumption maximum of 500 VA with peripherals	

Console design	
4 active probe ports	
Integrated HDD and DVD \pm R/W	
On board storage for BW printer	
Integrated speakers	
Probe holders	
Front handle	
Gel warmer (option)	
Rear handle (option)	

User interface

Operator Keyboard	
Ergonomic full size keyboard	
Swivel-adjustable, height-adjustable	
Digital TGC and digital A/N keyboard	
Physical A/N keyboard (option)	
10.4" LCD touch screen	

Monitor	
21.5" widescreen LCD with high resolution	

Applications	
Abdominal	
Obstetrical	
Gynecological	
Breast	
Small parts	
Musculoskeletal	
Vascular	
Urological	
Pediatric & neonatal	
Intraoperative	
Cardiac	
Transcranial	
Endocavitary (transvaginal, transrectal)	

Scanning Methods	
Electronic sector	
Electronic convex	
Electronic micro convex	
Electronic linear	
Real-time 4D volume sweep	

Transducer Types	
Sector phased array	
Convex array	
Microconvex array	
Linear array	
Matrix array	
Single CW (pencil) probes	
Volume probes (4D)	

Operating Modes	
B-Mode	
Coded harmonic imaging	
M-Mode	
Color Flow Mode (CFM)	
Power Doppler Imaging (PDI)	

System Overview (cont.)

Operating Modes (cont.)

PW Doppler with high PRF

M-Color Flow Mode

Anatomical M-Mode

Curved anatomical M-Mode

B-Flow™/B-Flow color (option)

Extended Field of View (LOGIQView Option)

Coded Contrast Imaging² (option)

CW Doppler Mode (option)

TVI Mode (option)

Elastography (option)

3D/4D Volume Modes (option)

System Standard Features

Advanced user interface with high resolution 10.4" wide LCD touch screen

Automatic optimization

CrossXBeam™ compounding

Speckle Reduction Imaging (SRI-HD)

Fine angle steering

Coded harmonic imaging

Virtual convex

Advanced 3D (option)

Patient information database

Image archive on integrated CD/DVD and hard drive

Raw data analysis

Real-time automatic doppler calculations

OB calculations

Fetal trending

System Options

Auto IMT

Advanced 3D

Cable hook rear

Card reader mounting kit

Elastography

Elastography Quantification³

System Options (cont.)

DICOM® 3.0 connectivity

LOGIQView

B-Flow/B-Flow Color

CF/PDI quantification (FlowQA)

Breast productivity package

Thyroid productivity package

Measure assist OB

AutoEF

B Steer+

Stress echo

Tissue Velocity Imaging (TVI) with Q-Analysis

Scan assistant

Compare assistant

Report writer

AFI cardiac strain

STIC

OmniView

Peripheral Options

Integrated options for

- Digital BW thermal printer
- HDMI output available for compatible devices
- S-Video output available for compatible devices
- Wireless LAN card for wireless data transfer
- External USB printer connection
- Power assistant (battery pack) for offline scanning

Digital color thermal printer

Foot switch with programmable functionality

Universal video converter

Console protective cover

Display Modes

Live and stored display format: full size and split screen – both with “thumbnails” for still and Cine

Review image format: 4x4 and “thumbnails” for still and Cine

Simultaneous capability

System Overview (cont.)

Display Modes (cont.)

B or CrossXBeam/PW

B or CrossXBeam/CFM or PDI

B/M

B/CrossXBeam

Real-time Triplex Mode (B or CrossXBeam + CFM or PDI/PW or CW (option))

Selectable Alternating Modes

B or CrossXBeam/PW

B or CrossXBeam + CFM (PDI)/PW(CW (option))

B/CW (option)

Multi-image (split/quad screen)

Live and/or frozen

B or CrossXBeam + B or CrossXBeam/CFM or PDI

Independent Cine playback

Timeline display

Independent dual B or CrossXBeam/PW display

CW

Display formats

- Top/bottom selectable format
- Side/side selectable format

Virtual convex

Timeline only

Display Annotation

Patient Name: first, last and middle

Patient ID

2nd patient ID

Age, sex and birth date

Hospital name

Date format:
3 types selectable

- MM/DD/YY
- DD/MM/YY
- YY/MM/DD

Time format:
2 types selectable

- 24 hours
- 12 hours

Gestational age from

- LMP
- GA
- EDD
- BBT

Display Annotation (cont.)

Displayed acoustic output

- TIS: Thermal Index Soft Tissue
- TIC: Thermal Index Cranial (Bone)
- TIB: Thermal Index Bone
- MI: Mechanical Index

% of maximum power output

Probe name

Map names

Probe orientation

Depth scale marker

Lateral scale marker

Focal zone markers

Image depth

Zoom depth

B-Mode

Gain

Dynamic range

Imaging frequency

Frame averaging

Acoustic frame rate

Gray map

SRI-HD

M-Mode

Gain

Dynamic range

Time scale

Doppler mode

Gain

Angle

Sample volume depth and width

Wall filter

Velocity and/or frequency scale

Spectrum inversion

Time scale

PRF

Doppler frequency

System Overview (cont.)

Display Annotation (cont.)

Color Flow Mode

Line density

Frame averaging

Packet size

Color scale: 3 types

- Power
- Directional PDI
- Symmetrical velocity imaging

Color velocity range and baseline

Color threshold marker

Color gain

PDI

Inversion

Doppler frequency

TGC curve

Cine gage, image number/frame number

Body pattern: multiple human and animal types

Application name

Measurement results

Operator message

Biopsy guide line and zone

Heart rate

General System Parameters

System Setup

Pre-programmable categories

User programmable preset capability

Factory default preset data

Languages: English, French, German, Spanish, Italian, Portuguese, Russian, Greek, Swedish, Danish, Dutch, Finnish, Norwegian, Japanese (message only)

OB report formats including Tokyo Univ., Osaka Univ., USA, Europe, and ASUM

User defined annotations

Body patterns

Customized comment home position

Reset

Complete User Manual Available On-Board Through Help (F1)

User manual and service manual are included on CD with each system. A printed manual is available upon request.

CINE Memory/Image Memory

776 MB of Cine memory

Selectable cine sequence for Cine review

Prospective Cine mark

Measurements/calculations and annotations on Cine playback

Scrolling timeline memory

Dual image Cine display

Quad image Cine display

Cine gauge and Cine image number display

Cine review loop

Cine review speed

Image Storage

On-board database of patient information from past exams

Storage formats:

- DICOM – compressed/uncompressed, single/multiframe, with/without raw data
- Export JPEG, JPEG2000, WMV, MPEG 4 and AVI formats

Storage devices:

- USB memory Stick: 64 MB to 4 GB (for exporting individual images/clips)
- CD-R storage: 700 MB
- DVD storage: -R (4.7 GB)
- Hard drive image storage: ~345 GB

Compare old images with current exam

Reload of archived data sets

Connectivity & DICOM

Ethernet network connection

DICOM 3.0 (option)

Wireless LAN (option)

Verify

Print

Store

General System Parameters (cont.)

Connectivity & DICOM (cont.)

Modality worklist

Storage commitment

Modality Performed Procedure Step (MPPS)

Media exchange

Off network/mobile storage queue

Query/retrieve

Public SR template

- Structured reporting – compatible with vascular and OB standard
- Direct export DICOM SR and XML

Remote capability InSite™ ExC

DICOM directory import

Physiological Input Panel (Option)

Physiological input

ECG, 2 lead

Dual R-Trigger

Pre-settable ECG R delay time

Pre-settable ECG position

Adjustable ECG gain control

Automatic heart rate display

Report Writer (Option)

On-board reporting package automates report writing

Formats various exam results into a report suitable for printing or reviewing on a standard PC

Exam result reports can include patient info, exam info, measurements, calculations, images, comments and physician diagnosis

Standard templates provided

Customizable templates

Thyroid reporting template

Scanning Parameters

Displayed imaging depth: 0 – 33 cm

Minimum depth of field: 0 – 2 cm (zoom) (probe dependent)

Maximum depth of field: 0 – 33 cm (probe dependent)

Scanning Parameters (cont.)

Continuous dynamic receive focus/continuous dynamic

Receive aperture

Adjustable dynamic range

Adjustable Field of View (FOV)

Image reverse: right/left

Image rotation of 0°, 180°

Digital B-Mode

Adjustable:

- Acoustic power
- Gain
- Dynamic range
- Frame averaging
- Gray scale map
- Frequency
- Line density
- Scanning size (FOV or angle – depending on the probe, see probe specifications)
- B colorization
- Reject
- Suppression
- SRI-HD
- Edge enhance

Digital M-Mode

Adjustable:

- Acoustic power
- Gain
- Dynamic range
- Gray scale map
- Frequency
- Sweep speed
- M colorization
- M display format
- Rejection

Anatomical M-Mode

M-Mode cursor adjustable at any plane

Can be activated from a Cine loop from a live or stored image

M and A capability

Available with Color Flow Mode

Curved Anatomical M-Mode

General System Parameters (cont.)

Digital Spectral Doppler Mode

Adjustable:	<ul style="list-style-type: none"> • Acoustic power • Gain • Dynamic range • Gray scale map • Transmit frequency • Wall filter • PW colorization • Velocity scale range • Sweep speed • Sample volume length • Angle correction • Steered linear • Spectrum inversion • Trace method • Baseline shift • Doppler auto trace • Time resolution • Compression • Trace direction • Trace sensitivity
-------------	--

Digital Color Flow Mode

Adjustable:	<ul style="list-style-type: none"> • Acoustic power • Color maps, including velocity-variance maps • Gain • Velocity scale range • Wall filter • Packet size • Line density • Spatial filter • Steering angle • Baseline shift • Frame average • Threshold • Accumulation mode • Sample volume control • Flash suppression • Quantification (option)
-------------	--

Digital Power Doppler Imaging

Adjustable:	<ul style="list-style-type: none"> • Acoustic power • Color maps including velocity-variance maps • Gain • Velocity scale range • Wall filter • Packet size • Line density • Spatial filter • Steering angle • Frame average • Threshold
-------------	---

Digital Power Doppler Imaging (cont.)

Adjustable (cont.):	<ul style="list-style-type: none"> • Accumulation mode • Sample volume control • Flash suppression
---------------------	---

Continuous Wave Doppler (Option)

Adjustable:	<ul style="list-style-type: none"> • Acoustic power • Gain • Dynamic range • Gray scale map • Transmit frequency • Wall filter • CW colorization • Velocity scale range • Sweep speed • Angle correction • Spectrum inversion • Trace method • Baseline shift • Doppler auto trace • Compression • Trace direction • Trace sensitivity
-------------	---

Automatic Optimization

Optimize B-Mode image to improve contrast resolution

Selectable amount of contrast resolution improvement (low, medium, high)

Auto TGC

Auto-spectral optimize adjusts	<ul style="list-style-type: none"> • Baseline • Invert • PRF (on live image) • Angle correction
--------------------------------	---

Coded Harmonic Imaging

Available on all 2D probes

B-Flow/B-Flow Color (Option)

Available on C1-5-RS, 8C-RS, L6-12-RS, 12L-RS, 9L-RS, ML6-15-RS, L8-18i-RS, L4-12t-RS, L10-22-RS, L3-9i-RS, E8CS-RS, and BE9CS-RS probes

Background: on/off

Sensitivity/PRI

Line density

Edge enhance

Frame average

Gray scale map

General System Parameters (cont.)

B-Flow/B-Flow Color (Option) (cont.)

Tint map

Dynamic range

Rejection

Gain

Dual beam

B-Flow Color

Accumulation

Coded Contrast Imaging (Option)

Available on C1-5-RS and 9L-RS probes

2 contrast timers

Timed updates: 0.05 – 10 seconds

Accumulation mode, six levels

Maximum Enhance Mode

Flash

Time Intensity Curve (TIC) Analysis

Auto MI control

The LOGIQ P9 is designed for compatibility with commercially available ultrasound contrast agents. Because the availability of these agents is subject to government regulation and approval, product features intended for use with these agents may not be commercially marketed nor made available before the contrast agent is cleared for use. Contrast related product features are enabled only on systems for delivery to an authorized country or region of use.

3D

Allows unlimited rotation and planar translations

3D reconstruction from Cine sweep

Advanced 3D (Option)

Acquisition of color data

Automatic rendering

3D landscape technology

3D movie

Scan Assistant (Option)

Factory programs

User defined programs

Scan Assistant (Option) (cont.)

Steps include image annotations, mode transitions, basic imaging controls and measurement initiation

Elastography (Option)

Available on C1-5-RS, L6-12-RS, 12L-RS, 9L-RS, ML6-15-RS, L4-12t-RS, E8CS-RS, and BE9CS-RS probes

Semi-Quantification²

TVI (Option)

Myocardial doppler imaging with color overlay on tissue image

Available on the sector probes

Tissue color overlay can be removed to show just the 2D image, still retaining the tissue velocity information

Curved anatomical M-Mode: free (curved) drawing of M-Mode generated from the cursor independent from the axial plane

Q-Analysis: multiple time motion trace display from selected points in the myocardium

Stress Echo (Option)

Advanced and flexible Stress Echo examination capabilities

Provides exercise and pharmacological protocol templates

8 default templates

Template editor for user configuration of existing templates or creation of new templates

Reference scan display during acquisition for stress level comparison (dual screen)

Baseline level/previous level selectable

Raw data continuous capture

Over 100 sec. available

Wall motion scoring (bull's-eye and segmental)

Smart stress: automatically set up various scanning parameters (for instance, geometry, frequency, gain, etc.) according to same projection on previous level

Virtual Convex

Provides a convex Field of View

Compatible with CrossXBeam

Available on all linear and sector transducers

General System Parameters (cont.)

SRI-HD

Speckle Reduction Imaging

Provides multiple levels of speckle reduction

Compatible with side-by-side DualView display

Compatible with all linear, convex and sector transducers

Compatible with B-Mode, color, contrast agent and 3D imaging

CrossXBeam

Provides 3, 5, 7 or 9 angles of spatial compounding

Live side-by-side DualView display

Compatible with:

- Color Mode
- PW
- SRI-HD
- Coded harmonic imaging
- Virtual convex

Available on C1-5-RS, 8C-RS, L6-12-RS, 12L-RS, 9L-RS, ML6-15-RS, L8-18i-RS, L4-12t-RS, L10-22-RS, L3-9i-RS, E8C-RS, E8CS-RS, BE9CS-RS, RIC5-9A-RS, and RAB2-6-RS probes

Controls Available While "Live"

Write zoom

B/M/CrossXBeam Mode

Gain

TGC

Dynamic range

Acoustic output

Transmission focus position

Transmission focus number

Line density control

Sweep speed for M-Mode

Number of angles for CrossXBeam

PW-Mode

Gain

Dynamic range

Acoustic output

Transmission frequency

PRF

Wall filter

Spectral averaging

Controls Available While "Live" (cont.)

Sample volume gate

- Length
- Depth

Velocity scale

Color Flow Mode

CFM gain

CFM velocity range

Acoustic output

Wall echo filter

Packet size

Frame rate control

CFM spatial filter

CFM frame averaging

CFM line resolution

Frequency/velocity baseline shift

Controls Available on "Freeze" or Recall

Automatic optimization

SRI-HD

CrossXBeam – display non-compounded and compounded image simultaneously in split screen

3D reconstruction from a stored Cine loop

B/M/CrossXBeam Mode

Gray map optimization

TGC

Colorized B and M

Frame average (loops only)

Dynamic range: Anatomical M-Mode

Max Read Zoom to 8x: baseline shift

Sweep speed

PW Mode

Gray map

Post gain

Baseline shift

Sweep speed

Invert spectral wave form

Compression

General System Parameters (cont.)

Controls Available on "Freeze" or Recall (cont.)

Rejection

Colorized spectrum

Display format

Doppler audio

Angle correct

Quick angle correct

Auto angle correct

Color flow

Overall gain (loops and stills)

Color map

Transparency map

Frame averaging (loops only)

Flash suppression

CFM display threshold

Spectral invert for Color/Doppler

Anatomical M-Mode on Cine loop

General Doppler Measurements/Calculations (cont.)

A/B ratio (velocities/frequency ratio)

PS (Peak Systole)

ED (End Diastole)

PS/ED (PS/ED ratio)

ED/PS (ED/PS ratio)

AT (Acceleration Time)

ACCEL (Acceleration)

TAMAX (Time Averaged Maximum Velocity)

Volume Flow (TAMEAN and vessel area)

Heart rate

PI (Pulsatility Index)

RI (Resistivity Index)

Real-time Doppler Auto Measurements/Calculations

PS (Peak Systole)

ED (End Diastole)

MD (Minimum Diastole)

PI (Pulsatility Index)

RI (Resistivity Index)

AT (Acceleration Time)

ACC (Acceleration)

PS/ED (PS/ED ratio)

ED/PS (ED/PS ratio)

HR (Heart Rate)

TAMAX (Time Averaged Maximum Velocity)

PVAL (Peak Velocity Value)

Volume Flow (TAMEAN and vessel area)

Measurements/Calculations

General B-Mode

Depth and distance

Circumference (ellipse/trace)

Area (ellipse/trace)

Volume (ellipsoid)

% Stenosis (area or diameter)

Angle between two lines

General M-Mode

M-Depth

Distance

Time

Slope

Heart rate

General Doppler Measurements/Calculations

Velocity

Time

OB Measurements/Calculations

Gestational age by:

- GS (Gestational Sac)
- CRL (Crown Rump Length)
- FL (Femur Length)
- BPD (Biparietal Diameter)
- AC (Abdominal Circumference)
- HC (Head Circumference)
- APTD x TTD (Anterior/Posterior Trunk Diameter by Transverse Trunk Diameter)
- FTA (Fetal Trunk cross-sectional Area)
- BD (Binocular Distance)

General System Parameters (cont.)

OB Measurements/Calculations (cont.)

Gestational age by (cont.):	<ul style="list-style-type: none"> HL (Humerus Length) FT (Foot Length) OFD (Occipital Frontal Diameter) TAD (Transverse Abdominal Diameter) TCD (Transverse Cerebellum Diameter) THD (Thorax Transverse Diameter) TIB (Tibia Length) ULNA (Ulna Length)
-----------------------------	--

Estimated fetal weight (EFW) by:	<ul style="list-style-type: none"> AC, BPD AC, BPD, FL AC, BPD, FL, HC AC, FL AC, FL, HC AC, HC BPD, APTD, TTD, FL BPD, APTD, TTD, SL
----------------------------------	---

Calculations and ratios	<ul style="list-style-type: none"> FL/BPD FL/AC FL/HC HC/AC CI (Cephalic Index) AFI (Amniotic Fluid Index) CTAR (Cardio-Thoracic Area Ratio)
-------------------------	---

Measurements/calculations by: ASUM, ASUM 2001, Berkowitz, Bertagnoli, Brenner, Campbell, CFEF, Chitty, Eik-Nes, Ericksen, Goldstein, Hadlock, Hansmann, Hellman, Hill, Hohler, Jeanty, JSUM, Kurtz, Mayden, Mercer, Merz, Moore, Nelson, Osaka University, Paris, Rempen, Robinson, Shepard, Shepard/Warsoff, Tokyo University, Tokyo/Shinozuka, Yarkoni

Fetal graphical trending

Growth percentiles

Multi-gestational calculations (4)

Fetal qualitative description (anatomical survey)

Fetal environmental description (biophysical profile)

Programmable OB tables

Over 20 selectable OB calculations

Expanded worksheets

GYN Measurements/Calculations

Right ovary length, width, height

Left ovary length, width, height

Uterus length, width, height

GYN Measurements/Calculations (cont.)

Cervix length, trace

Ovarian volume

ENDO (Endometrial Thickness)

Ovarian RI

Uterine RI

Follicular measurements

Summary reports

Vascular Measurements/Calculations

SYS DCCA (Systolic Distal Common Carotid Artery)

DIAS DCCA (Diastolic Distal Common Carotid Artery)

SYS MCCA (Systolic Mid Common Carotid Artery)

DIAS MCCA (Diastolic Mid Common Carotid Artery)

SYS PCCA (Systolic Proximal Common Carotid Artery)

DIAS PCCA (Diastolic Proximal Common Carotid Artery)

SYS DICA (Systolic Distal Internal Carotid Artery)

DIAS DICA (Systolic Distal Internal Carotid Artery)

SYS MICA (Systolic Mid Internal Carotid Artery)

DIAS MICA (Diastolic Mid Internal Carotid Artery)

SYS PICA (Systolic Proximal Internal Carotid Artery)

DIAS PICA (Diastolic Proximal Internal Carotid Artery)

SYS DECA (Systolic Distal External Carotid Artery)

DIAS DECA (Diastolic Distal External Carotid Artery)

SYS PECA (Systolic Proximal External Carotid Artery)

DIAS PECA (Diastolic Proximal External Carotid Artery)

VERT (Systolic Vertebral Velocity)

SUBCLAV (Systolic Subclavian Velocity)

Automatic IMT

Summary Reports

Urological Calculations

Bladder volume

Prostate volume

Left/right renal volume

Generic volume

Post-void bladder volume

Probes

LOGIQ P9

C1-5-RS, 8C-RS, E8C-RS, E8CS-RS, BE9CS-RS, 9L-RS, 12L-RS, L8-18i-RS, L6-12-RS, L4-12t-RS, L10-22-RS, L3-9i-RS, ML6-15-RS, 3Sc-RS, 6S-RS, 12S-RS, RAB2-6-RS, RIC5-9A-RS and P8D

C1-5-RS

Convex probe

Applications	Abdomen, Vascular, OB/Gyn, Urology
Biopsy guide	Multi-angle, disposable with a reusable bracket (H40432LE)

8C-RS

Micro convex probe

Applications	Neonatal, Pediatrics
Biopsy guide available	No

E8C-RS

Endocavitary micro convex probe

Applications	OB/GYN, Urology, Transvaginal, Transrectal
Biopsy guide	Single-angle, disposable with a disposable bracket (E8385MJ, E8333JB), single-angle, reusable bracket (H40412LN)

E8CS-RS

Endocavitary micro convex probe

Applications	OB/GYN, Urology, Transvaginal, Transrectal
Biopsy guide	Single-angle, disposable with a disposable bracket (E8385MJ, E8333JB), single-angle, reusable bracket (H40412LN)

BE9CS-RS

Endocavitary micro convex probe

Applications	Urology, Transrectal
Biopsy guide	Single-angle, disposable with a disposable bracket (E8387M, H42742LH, H42742LJ), single-angle, reusable bracket (E8387MA)

RAB2-6-RS

Convex volume probe

Applications	Abdomen, OB/GYN, Urology
Biopsy guide	Multi-angle, disposable with reusable bracket (H48681ML)

RIC5-9A-RS

Endocavitary micro convex volume probe

Applications	OB/GYN, Urology, Transvaginal, Transrectal
--------------	--

9L-RS

Linear probe

Applications	Vascular, Small Parts, Pediatric, Abdomen
Biopsy guide	Multi-angle, disposable with a reusable bracket (H4906BK)

12L-RS

Linear probe

Applications	Vascular, Small Parts, Neonatal, Pediatrics, Musculoskeletal
Biopsy guide	Multi-angle, disposable with a reusable bracket (H40432LC)

L8-18i-RS

Linear probe

Applications	Vascular, Small Parts, Neonatal, Pediatrics, Intraoperative
Biopsy guide	No

L6-12-RS

Linear probe

Applications	Abdomen, Vascular, Small Parts, Pediatrics, Neonatal, Musculoskeletal
Biopsy guide	Multi-angle, disposable with a reusable bracket (H40432LC)

Probes (cont.)

L4-12t-RS

Linear probe

Applications	Small Parts, Vascular, Pediatrics, Neonatal, Musculoskeletal
Biopsy guide	Multi-angle, disposable with a reusable bracket (H40432LC) single-angle, disposable with a reusable bracket (H48392LT: free hand, H48392LL: transverse)

L10-22-RS

Linear probe

Applications	Small Parts, Musculoskeletal , Neonatal
Biopsy guide	N/A

L3-9i-RS

Linear probe

Applications	Small Parts, Vascular, Musculoskeletal , Intraoperative
Biopsy guide	N/A

ML6-15-RS

Matrix array linear probe

Applications	Small Parts, Vascular, Neonatal, Pediatrics, Musculoskeletal
Biopsy guide	Multi-angle, disposable with a reusable bracket (H40432LJ)

3Sc-RS

Phased array sector probe

Applications	Cardiac, Transcranial, Abdomen
Biopsy guide	Multi-angle, disposable with a reusable bracket (H46222LC)

6S-RS

Phased array sector probe

Applications	Cardiac Neonatal, Pediatrics
Biopsy guide	No

12S-RS

Phased array sector probe

Applications	Pediatrics, Neonatal
Biopsy guide	N/A

RIC5-9A-RS (cont.)

Biopsy guide	Single-angle, disposable with a disposable bracket (H48681GF), single-angle, reusable bracket (H46721R)
--------------	---

P8D

CW split crystal probe

Applications	Cardiac, Vascular
--------------	-------------------

Inputs and Outputs

HDMI out

Ethernet network (RJ45)

S-video out

Composite video out

USB (2x in front, 3x in rear, 2x monitor)

AC power input

Safety Conformance

The LOGIQ P9 is:

Classified to UL 60601-1 by a nationally recognized test lab

Certified to CAN/CSA-C22.2 No. 601.1-M90 by an SCC accredited test lab

CE marked to council directive 93/42/EEC on medical devices

Conforms to the following standards for safety:	<ul style="list-style-type: none"> IEC 60601-1 2nd Edition Medical electrical equipment – Part 1: General requirements for safety IEC 60601-1 3rd Edition. General requirements for basic safety and essential performance IEC 60601-1-1 Medical electrical equipment – Part 1-1: General requirements for safety – Collateral Standard: Safety requirements for medical electrical systems
---	--

Safety Conformance (cont.)

The LOGIQ P9 is (cont.):

Conforms to the following standards for safety (cont.):

- IEC 60601-1-2 Medical electrical equipment – Part 1-2: General requirements for safety – Collateral Standard: Electromagnetic compatibility – requirements and tests
 - IEC 60601-1-4 Medical electrical equipment Part 1-4 General requirements for safety – Collateral Standard: programmable electrical medical systems
 - IEC 60601-1-6 Medical electrical equipment Part 1-6 General requirements for basic safety and essential performance – Collateral Standard: Usability
 - IEC 60601-2-37 Medical electrical equipment – Part 2-37: Particular requirements for the safety of ultrasonic medical diagnostic and monitoring equipment
 - ISO 10993-1 Biological evaluation of medical devices – Part 1 Evaluation and testing
 - NEMA UD2 Acoustic output measure standard for diagnostic ultrasound equipment
 - NEMA UD3 Standard for real time display of thermal and mechanical acoustic output indices on diagnostic ultrasound equipment (MI, TIS, TIB, TIC)
 - EMC Emissions Group 1 Class B device requirements as per Sub clause 4.2 of CISPR 11
 - EMC Emissions Group 1 Class A device requirements as per Sub clause 4.2 of CISPR 11 (Only with 6S-RS and RIC5-9A-RS)
-

1. The LOGIQ P9 is a highly mobile and easy to use, performance multi-purpose color doppler imaging system, designed for Abdominal, Small Parts, Musculoskeletal, Breast, Vascular, Cardiology, Transcranial, Urology, Pediatric, Neonatal, Obstetrics and Gynecology applications.
2. Contrast Enhanced Ultrasound is available in the U.S. for characterization of focal liver lesions and left ventricle opacity only.
3. Elastography with semi-Quantification (Elastography Quantification) described in this material has not been cleared by the U.S. FDA and is not available for promotion or sale in the United States.

Imagination at work

Product may not be available in all countries and regions. Full product technical specification is available upon request. Contact a GE Healthcare Representative for more information. Please visit www.gehealthcare.com/promotional-locations

Data subject to change.

© 2016 General Electric Company.

GE, the GE Monogram, imagination at work, LOGIQ, B-Flow, InSite and CrossXBeam are trademarks of General Electric Company.

DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information.

GE Medical Systems Ultrasound & Primary Care Diagnostics, LLC, a General Electric company, doing business as GE Healthcare.

Reproduction in any form is forbidden without prior written permission from GE. Nothing in this material should be used to diagnose or treat any disease or condition. Readers must consult a healthcare professional.

